Ather 450X specifications.

Ather 450X

Ather 450 Plus

Performance

Power (continuous / peak)
Max torque
Top speed
Acceleration (0-40 km/h)
Gradeability
Riding modes
Motor type
Ingress protection (motor)
Ingress protection (controller)

3.3 kW / 6 kW 26 Nm 80 km/h 3.3 s 20 degrees Warp | Sport | Ride | Eco PMSM IP66 IP65 3.3 kW / 5.4 kW 22 Nm 80 km/h 3.9 s 18 degrees Sport | Ride | Eco PMSM IP66

Range

TrueRange™ (Ride) TrueRange™ (Eco) Range (Indian Drive Cycle)

70 km 85 km 116 km 60 km 70 km 100 km

Charging

Char	ging	unit

0-80% (home charging) 0-100% (home charging) Fast charging rate (0-50% SOC) Fast charging rate (50-80% SOC) Ather Dot (or) Portable charger 3 h 35 min 5 h 45 min 1.5 km/min 1 km/min

Ather Dot (or) Portable charger 3 h 35 min 5 h 45 min 1 km/min 1 km/min

Battery

Installed capacity Usable capacity Battery type Water & dust resistance Pack casing 2.9 kWh 2.6 kWh Lithium-ion, 21700 cell IP67 Aluminium alloy 2.9 kWh 2.23 kWh Lithium-ion, 21700 cell IP67 Aluminium alloy

Ather 450X

Ather 450 Plus

Transmission

Type Transmission ratio Belt drive 7:8:1

Tyres & wheels

Wheel type Wheel size (front) Wheel size (rear) Tyre size (front) Tyre size (rear) Alloy wheels 30.48 cm x 5.46 cm (12" x 2.15") 30.48 cm x 6.35 cm (12" x 2.5") 90/90-12 tubeless 90/90-12 tubeless

Brakes

Braking system Brake type (front) Brake type (rear) Disc size (front) Disc size (rear) Braking distance (60-0 km/h)

Combined braking system & regenerative braking Hydraulically actuated triple-piston calliper disc Hydraulically actuated single-piston calliper disc

200 mm 190 mm 28.6 m

Suspension

Front suspension Rear suspension Telescopic forks Symmetrically mounted progressive mono-schock

Peripherals

Headlights	LED
Taillights	LED
Indicators	LED with auto turn-off feature
Parking assist	Reverse Assist

Colours

White Space Grey Mint Green

Ather 450X

Ather 450 Plus

Dime		- 0 -	L	
I)IMA	nsion		TOPE	ade

Kerb weight	108 kg
F:R weight ratio	48:52
Seat height	780 mm
Boot capacity	221

Display + touchscreen dashboard

Processor Operating system Screen size & type Water & dust resistance

Snapdragon 212 Quadcore 1.3Ghz, 1GB RAM, 8GB storage Android Open Source OS (AOSP) 17.78 cm (7") TFT, LED-backlit, capacitive touch IP65

Smart features

Positioning system

GNSS with AGPS 4G LTE Cat-4 / 4G LTE Cat-4 / WCDMA/EDGE WCDMA/EDGE Bluetooth 4.2, BLE 5.0 Over-the-air-updates **Onboard navigation** Auto indicator off Side stand sensor Guide-me-home lights Connected mobile app Time based adaptive screen brightness & themes

GNSS with AGPS

Connectivity	
Bluetooth	
Dashboard	

App based smart features

Mobile app

Smart accessories support

Ride Stats Push navigation Live location & vehicle state tracking Music & call control * Welcome lights **Tyre Pressure Monitoring** System (TPMS)

Ride Stats Push navigation Live location & vehicle state tracking

*Will be implemented soon through over-the-air updates.



www.atherenergy.com

*All trademarks are the property of their respective owners.

*Ather reserves the right to alter specifications, designs or add / delete features without prior notice and without liability. *All internet / connected features will be available only if one has subscribed to the Ather Connect subscription plan. *Please refer to the website for detailed Terms and Conditions.